



Parts Details



Wear Resistance PU Wheel



Foot Brake



Foot Pedal To Lift Up



Hydraulic Oil Cylinder



Collapsible Handle



Q235b High Quality Steel Plate

Specification

Model	Platform Size(mm)	Lifting Range(mm)	Lifting Capacity(kg)	Self Weight(kg)
PT150	700*450*35	210-720	150	40
PT300	810*500*50	280-900	300	71
PT500	810*500*50	280-900	500	75
PT800	1016*570*60	415-1000	800	100
PT1000	1200*610*80	380-1000	1000	161
PTD1500	1200*610*80	380-1000	1500	177
PTD2000	1200*610*80	380-1000	2000	177
PTS150	700*450*35	305-1260	150	51
PTS350	905*500*50	350-1300	350	99
PTS500	905*500*50	360-1500	500	107
PTS800	1200*610*58	450-1500	800	142
PTS1000	1200*610*80	500-1700	1000	229
PTS1500	1200*610*80	500-1700	1500	280
PTH500	950*500*50	530-2000	500	130

Manual Mobile Scissor Lift Table

Manual scissor lift table is made of high strength steel, internal safety valve, fully sealed oil cylinder. The manual scissor lift table has reasonable design and structure, safe and stable, reliable, easy to operate characteristics. Equipped with nylon guide wheel to save the operator's physical strength, and can protect the load wheel and pallet load wheel. Unique hydraulic pump design, simple pump for pipeline loading and unloading operation to maintain an ideal height and design; The unique ergonomic design makes the operator comfortable to operate.



Electric Mobile Scissor Lift Table

The electric Scissor Lift Table is based on the manual Scissor Lift Table, which can be divided into electric lifting and manual operation and full electric driving type.

It is more efficient and easier to use than the manual Scissor Lift Table.



Parts Details



Arc Caster With Side Brake



Up And Down Buttons



Battery Indicator



Emergency Stop



Walking Control



Operating Handle

Specification

	DPS350	DPS500	DPS800	DPS1000
Load Capacity (kg)	350	500	800	1000
Min. Height (mm)	360	360	500	500
Max. Height (mm)	1500	1500	1700	1700
Table Dimension (mm)	905*500*50	905*500*50	1200*610*50	1200*610*50
Dia. of the wheel (mm)	Φ125	Φ125	Φ150	Φ150
Voltage (V)	12	12	12	12
Power (kw)	0.8	0.8	0.8	1.6
Dstorage Battery (Ah)	60	60	120	120
Charger input Voltage (V)	220/110	220/110	220/110	220/110
Net Weight (kg)	140	140	290	290

	DP350	DP500	DP800	DP1000
Load Capacity (kg)	300	500	800	1000
Min. Height (mm)	280	280	410	410
Max. Height (mm)	900	900	1000	1000
Table Dimension (mm)	950*500*50	950*500*50	1200*610*50	1200*610*50
Dia. of the wheel (mm)	Φ125	Φ125	Φ150	Φ150
Voltage (V)	12	12	12	12
Power (kw)	0.8	0.8	0.8	0.8
Dstorage Battery (Ah)	60	60	60	120
Charger input Voltage (V)	220/110	220/110	220/110	220/110
Net Weight (kg)	110	110	150	150